



AcrPrimer

Water based Acrylic primer

Description

SPARTAN AcrPrimer is used as a primer, sealer and bonding agent to prepare wall and floor surfaces prior to the application of waterproofing membrane and wall coating system.

Uses

- To act as a bonding agent to old floors.
- To use as a bonding agent on smooth concrete finishes.
- Can be used as a pore sealer on rough porous concrete to eliminate air bubbles appearing.

Advantages

- Easy to apply.
- Excellent penetration, to seal pores and capillaries.
- To reduce dust, increase abrasion resistance of substrate.

Technical Data

Physical Properties

Specific gravity	1.01
Spread of fire	Non - flammable
Drying time	30 minutes
Water resistance	Very Good

Surface Preparation

- Ensure that surfaces are dry and clean and free from curing compound or release agents.
- No chipping or roughening of surface is required if the condition is stable. Old paint work which are stable can remain.
- Any contamination including commercial detergents used for cleaning must be thoroughly rinsed off with plenty of water.

Application

Apply SPARTAN AcrPrimer to clean form floor with roller, brush or squeegee. Allow to dry till clear film appears. Primer is dry when all milkiness disappears.

Coverage

8 - 10m² per litre, subject to the actual site condition.

Packaging

20 Litres/ pail

Shelf Life

Shelf of up to 12 months from the date of manufacture. Store in a cool place away from direct sunlight. Avoid freezing of the primer.

Health and Safety

SPARTAN AcrPrimer is non toxic. In case of excessive skin contact, thoroughly flush with clean water. If still effects occur, seek medical attention promptly.

SPARTAN