

D-LAM 20

TDS39 Rev1 01/04/09

Controlled Paint Removal Material

DESCRIPTION

D-LAM 20 is a solvent based paint removal system in an easy to use paper pulp carrier.

USES

Used to remove paint coatings from timber, plaster and masonry. By timing the application paint can be removed 1 coat at a time or several coats together. The D-LAM 20 is ideal for exposing heritage stencil work that has been hidden by numerous coats of paint and graffiti removal.

FEATURES

- ✓ Non caustic
- ✓ Controllable
- ✓ Can be used on most substrates
- ✓ Non methylene chloride
- ✓ Self Neutralising
- ✓ Easy to use

TECHNICAL DATA

S.G.	1.02 – 1.04
Flashpoint (deg C)	52 (Pmcc)
Miscible with water	

APPLICATION

Apply D-LAM 20 by trowel at approximately 3 to 4mm thickness. Reaction time can be as short as 20 minutes for 1 coat removal and 24 hours to remove up to 6 coats.

After the required dwell time, remove the D-LAM 20 from the surface and avoid removing the coating, place the D-LAM 20 into a bucket and mix 50/50 with fresh D-LAM 20 ready to use again. Remove the softened paint separately and dispose of in the appropriate manner. Reapply the remixed D-LAM 20 and repeat procedure until the desired removal is completed.

It is advisable to apply a test area prior to the commencement of each project to assess its suitability and most affective application method.

CLEAN UP

Wash all equipment in water.

PACKAGING

Container Size: 4 Litre and 20 Litre containers.

SAFETY

Refer to Westlegate Pty Ltd Material Safety Data Sheet (MSDS) for instructions.



Westlegate Pty Ltd
287 Milperra Road, Revesby NSW 2212
Ph: 61 2 97744100 Fax: 61 2 97744626
Email: westox@ozemail.com.au Website: www.westox.com