

GLOSSTEX

TDS04 Rev2 01/04/09

High Build Gloss Profiled Coating

DESCRIPTION

A high gloss finish with a low dirt retention, maximum protection and exceptional longevity.

USES

An aesthetically pleasing architectural texture finish coating for both interior and exterior use.

FEATURES

- ✓ Wide colour range.
- ✓ Waterbased, no mixing required.
- ✓ UV stable, high gloss texture finish.
- ✓ Does not chalk.
- ✓ Outstanding flexibility.
- ✓ Exceptionally durable.
- ✓ Low dirt retention.

TECHNICAL DATA

Volume Solids	53% \pm 0.5%
Specific Gravity	1.15 \pm 0.05
Elongation to break	350% @ 20°C
Adhesion to substrate	25.4Kgf / cm ²

PREPARATION

- ✗ Do not apply coating if temperature is below 10°C or above 35°C.
 - ✗ Do not apply coating if rain is imminent. Sound paint may be overcoated.
- Not recommended for below grade waterproofing.
New concrete should be a minimum of 28 days old before application commences.
All holes and cracks are to be repaired prior to coating.
The surface to be treated should be clean and sound, free of oil, grease, flaking paint, laitance and material deleterious to the adhesion of the coating system.

APPLICATION

Application by brush, roller or spray to the prepared pre-primed surface at the rate of 3m² per Litre.

Apply **second coat** at 1m² per Litre, allowing a minimum four (4) hour drying period between coats.

CLEAN UP

Wash all equipment in fresh water immediately after use.

PACKAGING

Container Size - 15 Litre containers.

SAFETY

Refer to Westlegate Pty Ltd Material Safety Data Sheet (MSDS) for instructions.