

WESPRIME

TDS38 Rev1 01/04/09

DESCRIPTION

A cost effective resin rich primer based on a pure acrylic resin.

USES

Wesprime is a premix primer. It is an excellent primer for cement roof tiles, cement render and concrete substrates that are to be coated with Westox Colourcote, Satintex, Glosstex or Wesdex. Wesprime can also be used as a clear Glazecoat over Colourcote.

PREPARATION

All surfaces to be coated must be clean, dry and free of any material that may affect the adhesion of the primer. Repair any unsound substrate prior to coating.

APPLICATION

No mixing required. Apply by brush, roller or spray. If unsure of adhesion, carryout a small test section prior to full application. Allow primer to dry for a minimum 1 hour @ 25°C before applying top coats (a longer cure time will be required in lower temperatures).

PROPERTIES

Drying Time	Approximately 20 mins @ 25°C
Recoat Time	Approximately 1 hour @ 25°C
Solids as supplied	25% + - 3%
Coverage	5 to 6m ² per Litre

CLEAN UP

Clean all equipment in water.

PACKAGING

Container Size 1 Litre, 4 Litre, 10 Litre & 20 Litre

SAFETY

Refer to Westlegat Pty Ltd Material Safety Data Sheet (MSDS) for instructions.



Westlegat Pty Ltd
287 Milperra Road, Revesby NSW 2212
Ph: 61 2 97744100 Fax: 61 2 97744626
Email: westox@ozemail.com.au Website: www.westox.com